














Technical specifications

Coral Luxe (29xx)		
	Total thickness	ISO 1765 Approx. 8,5 mm
	Wear classification	EN1307 31, commercial light
Available sizes (all sizes are approx.) Luxe series 29xx, 6 colors		
		Rolls
	Roll sizes with 2,5cm edge each side Rolls FR have no edges	105 cm
	Mat sizes with 2,5cm edge all sides	135 x 205 cm
Roll length approx. 20 m		
	Suitability for castor chairs	EN 985 No
Color fastness ratings:		
	Light	EN ISO 105/B02 8
	Rubbing	EN ISO 105/X12 4-5
	Water	EN ISO 105/E01 4-5
	Seawater	EN ISO 105/E02 4-5
	Waterstains	EN 1307 annex G 5
	Shampoo	BS 1006 4
	Organic solvents	EN ISO 105/X05
	Antistatic properties	ISO 10965
Manufacturing method/type		Tufted, 5/32" cut-pile
Designs		Plain colored
Pile material		100% polyamide
Tuft base		Non-woven polyester
Backing		EVERFORT vinyl
	Total weight	ISO 8543 Approx. 4100 gram/m ²
	Pile installation weight	ISO 8543 Approx. 1000 gram/m ²
	Pile thickness	ISO 1766 Approx. 5,5 mm
	Pile density	ISO 8543 0,14 gram/cm ³
	Number of tufts	ISO 1763 Approx. 93.000/m ²
	Suitability for stairs	EN 1963 No
	Comfort class	EN 1307 LC3
<div> <div>EN 14041</div> <div>CE</div> <div>1300178_DoP-408</div> </div>		
All Coral products meet the requirements of EN 14041, excluding loose-laid mats and rugs		
	Fire behaviour	EN 13501-1 B _s -s1
	Slip resistance	EN 13893 DS
	Personal charging	ISO 6356 < 2 kV

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.
All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.
The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

